



Part Numbers  
**RVS20, RVS10, RVS5A,  
 RVS10S, RVS5S.**

**RITCH™ HEAVY DUTY AXLE STANDS.**

**RITCH™ HEAVY DUTY AXLE STANDS.**

- Manufactured to comply with AS/NZS 2538-1995.
- One piece base for stability
- Heavy duty welded construction.
- Pin style lock device with safety chain.
- Fitted with auxiliary wheels for ease of mobility where applicable.
- Sold and rated as a single stand.
- Fabricated in Australia.

RVS10



RVS20



RVS10S



Part Number	Working Load Limit.	Closed Height	Maximum Height	Base Size	Net Weight
RVS5A	5,000Kg	440mm	690mm	360mmx360mm	17Kg
RVS5AS	5,000Kg	275mm	425mm	300mmx300mm	13Kg
RVS10	10,000Kg	440mm	690mm	360mmx360mm	25Kg
RVS10S	10,000Kg	280mm	430mm	300mmx300mm	16Kg
RVS20	20,000Kg	800mm	1200mm	600mmx600mm	85Kg



**Screw Type Axle Stand**

Part Number

**LVS3S**



**FEATURES**

Reinforced fabricated steel provides maximum safety under load. Heavy duty thread which allows fine adjustment without moving the load. Heavy duty head cap for safe and easy location.

Manufactured to comply to Australian Standards AS/NZS 2538:1995 where applicable.

<b>SPECIFICATIONS</b>	<b>LVS3S</b>
Working Load Limit	3,000kg
Closed Height	310mm
Maximum Height	500mm
Base Size	230mm
Net Weight	8.5kg/pr



**Ratchet Type Axle Stand**

Part Number

**LVS3R, LVS5R  
LVS8R**



**FEATURES**

Welded steel construction for safety and strength. Heavy duty head cap for ease of location, wide base for stability.

Manufactured to comply to Australian Standards AS/NZS 2538:1995 where applicable.

SPECIFICATIONS	LVS3R	LVS5R	LVS8R
Working Load Limit	3,000kg	5,000kg	8,000kg
Closed Height	295mm	394mm	445mm
Maximum Height	433mm	622mm	700mm
Base Size	190mm x 225mm	266mm x 300mm	307mm x 274mm
Net Weight	11.6kg/pr	18.3kg/pr	26.1kg/pr